



AREMO-2175PA

19" 2U industrial rack-mount chassis for PICMG backplane



The AREMO-2175PA, 19" 2U Rack-mount, designed for PICMG 1.3 can support 6-slot backplane that also builds two hot-swap 3.5"SATA HDD driver bays and two USB interface on front panel. AREMO-2175PA can equip high wattage PS/2 form factor PSU. The build-in replaceable air filters are for easy maintenance. AREMO-2175PA is suitable for Factory and Server applications.

FEATURES

- One slim CD-ROM and two hot-swap 3.5" HDD (SATA) Drive bays
- Two USB ports on the front panel
- Two 7cm ball-bearing cooling fans for better ventilation
- PS/2 or Mini-redundant power supply installable
- One power On/Off switch with protection cap and one touch free reset for secure access

ORDERING GUIDE

- **AREMO-2175-PA**
19" 2U rack-mount chassis for PICMG backplane
- **AREMO-2175-PA/B**
19" 2U black rack-mount chassis for PICMG backplane

GENERAL

| | |
|--------------------|---|
| Construction | Heavy-duty steel |
| Drive Bay Internal | 1x 3.5" HDD |
| Drive Bay External | 1x Slim type CD-ROM, 2x Hot-swap 3.5" HDD |
| Card Retainer | Two locations for one card retainer |
| Air Filter | One external replaceable air filter |
| Cooling Fan | Two 7cm ball-bearing fans |
| Indicator | 1x HDD+ 1x Power On/Off |
| Switch | 1x Power On/Off (with a protection cap), 1x System reset |
| Connector | 2x USB ports on the front panel |
| Standard Color | Beige, Black |
| Dimension | 482(W) x 429.2(D) x 88.6(H) mm |
| Weight | 11 kg |
| Backplane | PBPE-06V464: 6-slot [PCIe (1), PCI (0), PCI-X (4)] PCIMG 1.3 backplane PBPE-06V3: 6-slot [PCIe (2), PCI (3), PCI-X (0)] PCIMG 1.3 backplane PBPE-06V: 6-slot [PCIe (5)] PCIMG 1.3 backplane |

POWER SUPPLY

| | |
|--------------------------|---|
| Maximum output | 500W active PFC |
| Output Voltage & Current | + 5V@22A; +12V1@20A; +12V2@25A; +3.3V@10A; -12V@0.3A, +5Vsb@2.5A |
| Input Voltage | 90V ~ 264V AC, full range |
| Input Frequency | 50 ~ 60Hz |
| Input Current | 10A@110V, 5A@240V |
| Efficiency | > 80% |
| MTBF | 100,000 hrs |
| EMI & Safety Approval | UL, TUV, CE, FCC, CB, CCC, BSMI, BIS |

ENVIRONMENT

| | |
|-----------------------|--|
| Operating Temperature | 0°C ~ 50°C |
| Storage Temperature | 0°C to 85°C |
| Relative Humidity | Heavy-duty steel |
| Vibration | 5~7 Hz: 0.5" double amplitude displacement 7~2000 Hz: 1.5g acceleration |

AREMO-2175PA

19" 2U industrial rack-mount chassis for PICMG backplane

| FEATURE | BENEFITS |
|--|---|
| <ul style="list-style-type: none"> 500W Active PFC power supply | <ul style="list-style-type: none"> Sufficient power source for Intel® Desktop Platform |
| <ul style="list-style-type: none"> Two 7cm high speed fans | <ul style="list-style-type: none"> Better ventilation to enhance system reliability |
| <ul style="list-style-type: none"> Two swappable SATA HDD drive bays | <ul style="list-style-type: none"> Easy to access HDD drives |
| <ul style="list-style-type: none"> Four Low profile PCI expansion slots | <ul style="list-style-type: none"> For system function expansion |
| <ul style="list-style-type: none"> Front replaceable air filters | <ul style="list-style-type: none"> Easy maintenance |

REFINEMENT



Thumb Lock

Convenient to operate or protect the system




Two Swappable SATA HDD Drives

Easy to access HDD drives




Front Replaceable Air Filters/Fans

Convenient to change air filters or fans when needed



Rear View

MECHANICAL DRAWING



Unit: mm