

ORION-D3501P

350W PS/2 ATX power supply with active PFC



SPECIFICATION

Input Voltage	90V ~ 264V AC, full range
Input Frequency	47 ~ 63 Hz
Input Current	6A@90V
Efficiency	> 68%
Holdup Time	17 ms. at full load @25°C
Over Voltage Protection	+5V: 7V; +3.3V: 4.3V; +12V: 15.6V
Over Power/Load Protection	Output power over to 110%~140%
MTBF	75,145 hrs
EMI & Safety Approval	UL, TUV, CE, FCC, CB, CSA, SEMKO, FIMKO, NEMCO, DIMCO
Temperature/Humidity	Operating: 0 ~ 50°C, 20 ~ 85%RH Storage: -40 ~ 70°C, 10 ~ 90%RH
Dimension (WxDxH)	150 x 140 x 86 mm; 5.9" x 5.5" x 3.4"

FEATURES

- PS/2 ATX power supply, suitable for 2U, node chassis, and larger chassis
- Active PFC, full-range input
- Total output power of +5V,+3.3V and +12V is 326W
- Max. +12V load output is 18A

ORDERING GUIDE

- **ORION-D3501P**
350W PS/2 ATX power supply with active PFC

DC OUTPUT

	+5V	+3.3V	+12V	-5V	-12V	+5Vsb
Max. Load	18A	20A	18A	0.3A	0.5A	2.5A
Min. Load	1A	1A	1A	0A	0A	0A
Load Reg.	±5%	±5%	±5%	±10%	±10%	±5%
Line Reg.	±1%	±1.5%	±1%	±2.4%	±1%	±1%
Ripple	±1%	±1.5%	±0.8%	±3%	±1.25%	±1%
Noise	±1%	±1.5%	±0.8%	±3%	±1.25%	±1%

ORION-D4601P

460W PS/2 ATX power supply with active PFC



SPECIFICATION

Input Voltage	90V ~ 264V AC, full range
Input Frequency	47 ~ 63 Hz
Input Current	9A@115V, 5A@230V
Efficiency	> 60%
Holdup Time	16 ms at full load
Over Voltage Protection	+5V: 5.7 ~ 7.0V; +3.3V: 3.9 ~ 4.5V; +12V: 13.6 ~ 16.0V
Over Power/Load Protection	Output power over 110% ~ 150%
MTBF	100,000 hrs
EMI & Safety Approval	UL, TUV
Temperature/Humidity	Operating: 0 ~ 40°C, 20 ~ 85%RH Storage: -20 ~ 60°C, 5 ~ 95%RH
Dimension (WxDxH)	150 x 140 x 86 mm; 5.9" x 5.5" x 3.4"

FEATURES

- PS/2 ATX power supply suitable for 2U and larger chassis
- Active PFC, full-range input
- Support Intel® Pentium® 4 processor
- Max. +5V load output is 20A

ORDERING GUIDE

- **ORION-D4601P**
460W PS/2 ATX power supply with active PFC

DC OUTPUT

	+5V	+3.3V	+12V	-12V	+5Vsb
Max. Load	20A	22A	16A	0.5A	2.5A
Min. Load	0.5A	0.3A	1A	0A	0A
Reg.	±5%	±5%	±5%	±10%	±5%
Ripple	50mv	50mv	120mv	120mv	50mv
Noise	50mv	50mv	120mv	120mv	50mv