

# ORION-D5501P

550W PS/2 ATX power supply with active PFC



## FEATURES

- PS/2 ATX power supply suitable for 2U and larger chassis
- Active PFC, full-range input
- Support Intel® Pentium® 4 processor
- Max. +5V load output is 29A

## ORDERING GUIDE

- **ORION-D5501P**  
550W PS/2 ATX power supply with active PFC

## DC OUTPUT

	+5V	+3.3V	+12V	-5V	-12V	+5Vsb
<b>Max. Load</b>	29A	27A	18A	0.3A	0.8A	2A
<b>Min. Load</b>	3A	0.4A	1A	0A	0A	0A
<b>Reg.</b>	+5% -4%	+5% -4%	+5% -4%	±10%	+9% -5%	+5% -4%
<b>Ripple</b>	50mV	50mV	120mV	120mV	120mV	50mV
<b>Noise</b>	50mV	50mV	120mV	120mV	120mV	50mV

## SPECIFICATION

Input Voltage	90V ~ 264V AC, full range
Input Frequency	47 ~ 63 Hz
Input Current	9.5A@115V, 5.5A@230V
Efficiency	> 60%
Holdup Time	16 ms at full load
Over Voltage Protection	+5V: 5.7 ~ 7.0V; +3.3V: 3.9 ~ 4.5V; +12V: 13.6 ~ 16.0V
Over Power/Load Protection	Output power over 110% ~ 150%
MTBF	100,000 hrs
EMI & Safety Approval	UL, cUL, TUV, CE, FCC
Temperature/Humidity	Operating: 0 ~ 40°C, 20 ~ 90%RH Storage: -20 ~ 60°C, 5 ~ 95%RH
Dimension (WxDxH)	150 x 165 x 86 mm; 5.9" x 6.5" x 3.4"

# ORION-300DX/24/48

300W -48V/24V DC input DC/DC PS/2 ATX power supply



## FEATURES

- PS/2 ATX power supply suitable for 2U and larger chassis
- ORION-300DX/24 for +24V DC input, suitable for vehicle applications
- ORION-300DX/48 for -48V DC input, suitable for telecommunication applications
- Max. -12V output is 2A, suitable for CTI application

## ORDERING GUIDE

- **ORION-300DX/48**  
300W -48V DC input DC/DC PS/2 ATX power supply
- **ORION-300DX/24**  
300W 24V DC input DC/DC PS/2 ATX power supply

## DC OUTPUT

	+5V	+3.3V	+12V	-5V	-12V	+5Vsb
<b>Max. Load</b>	30A	15A	15A	2A	2A	1.2A
<b>Min. Load</b>	2A	0.3A	0.5A	0A	0A	0A
<b>Load Reg.</b>	±5%	±3%	±5%	±10%	±5%	±5%
<b>Cross Reg.</b>	±5%	±3%	±5%	±10%	±5%	±5%
<b>Line Reg.</b>	±1%	±1%	±1%	±1%	±1%	±1%
<b>Ripple</b>	±1%	±1.5%	±1%	±2%	±1%	±1%
<b>Noise</b>	±1%	±1.5%	±1%	±2%	±1%	±1%

## SPECIFICATION

Input Voltage	-40V~-72V DC for ORION-300DX/48 19V~32V DC for ORION-300DX/24
Input Current	10A@-48V, 20A@24V DC input
Efficiency	> 65%
Holdup Time	16 ms
Over Voltage Protection	+5V: 5.7 ~ 7.0V
MTBF	100,000 hrs
EMI & Safety Approval	UL, TUV, CSA
Temperature/Humidity	Operating: 0 ~ 40°C, 10 ~ 90%RH Storage: -60 ~ 70°C, 5 ~ 95%RH
Dimension (WxDxH)	150 x 140 x 86 mm; 5.9" x 5.5" x 3.4"